Revised: 4/2007

## DRIVEWAY SIGHT DISTANCE

(Department of Public Works)

Road Name: (County or Preference	Road)	(Route No.)			
Project / Property:					
Address:					
County File #:					
Inspected by:	Date				
			Vicinity Map: 1" = 2,000'		
Existing surface:	Width:	Type:	Condition:		
Existing shoulder / adjacent:	Width:	Type:	Condition:		
Existing shoulder / opposite:	Width:	Type:	Condition:		
Posted Speed:	Minimum Required Sight Distance 1:				
Actual Sight Distance – Left <sup>2</sup> : _	- Left <sup>2</sup> : Actual Sight Distance - Right <sup>2</sup> :				
Notes/Conditions/Driveway dist	ance from land	mark:			

Posted	Assumed	INTERSECTION SIGHT DISTANCE REQUIRED (FT)				
Speed	Design Speed	One Lane	Two Lanes	Three Lanes		
(mph)	(mph)	Crossed	Crossed	Crossed		
25	35	390	415	440		
30	40	445	475	500		
35	45	500	530	565		
40	50	555	590	625		
45	55	610	650	690		
50	60	665	710	750		
55	65	720	765	815		

Minimum Required Sight Distance <sup>1</sup>

- <sup>2</sup>Sight distances are measured using a height of eye of 3.5 feet, height of object of 3.5 feet and the following setbacks from the edge of the county roadway:

For Single Use Driveways onto existing roadways:
For Use-In-Common Driveways:
10 feet
15 feet

- Reference A.A.S.H.T.O. A Policy on Geometric Design of Highways and Street, 2004 version