

STORMWATER MAINTENANCE SCHEDULE

NON-ROOFTOP DISCONNECTION

“WIDE SHOULDER TECHNIQUE”

MODIFIED TO CORRESPOND TO CARROLL COUNTY DETAILS

MONTHLY INSPECTION		
Inspection Item	Inspection Requirements	Remedial Action
Vegetative Cover and Erosion	Check for vegetation over 4” height. Check disconnection area for channelizing and bare spots.	Mow grass/remove trees and shrubs. Re-grade if concentrated flow is causing rills or gulying on surface. Re-seed as necessary.
SEASONAL INSPECTION AND AFTER A MAJOR STORM		
Inspection Item	Inspection Requirements	Remedial Action
Inflow	Ensure sheet flow from pavement to grass shoulder disconnection area.	Remove debris, vegetation, regrade and re-seed as necessary to ensure sheet flow from pavement.
Dewatering	Check for soft areas and/or soil saturated to the surface,	Check slotted pipe, rodent guards and eliminate blockages. If necessary, excavate, remove and replace stone and slotted pipe.
ANNUAL INSPECTION		
Inspection Item	Inspection Requirements	Remedial Action
Overall Function of Disconnection	Check that grass disconnection is operating as designed.	Repair to good condition according to specifications on the approved plans.

Modified from Drywell Maintenance Schedule
Martin B. Covington, III, P.E.
Carroll County Stormwater Management
Program Engineer
July 8, 2020